

PROCURVE™

1 Product Name

PROCURVE™

2 Manufacturer

Custom Building Products
13001 Seal Beach Blvd.
Seal Beach, CA 90740-2757
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Fax: 800- 200-7765
Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

Curved designs are a snap with ProCurve™, a flexible profile for tile installations or other designs with wavy, meandering edges. Let your imagination run wild—ProCurve™ gives you the freedom to bend, curve, and twist without sacrificing edge protection or an aesthetic finish.

Composition of Product

- Aluminum (anodized or powder-coated)
- Solid brass
- High quality stainless steel 1.4301 (V2A)

Sizes

Material	Length (m)	Height (mm)
Plain Aluminum	2.5	15-Mar
Plain Brass	2.5	15-Mar
Brilliant Stainless Steel	2.5	3 - 12.5

Benefits of Product in the Installation

- PROCURVE square-edged profiles are easy to fit. They protect edges and enhance the overall image of surfaces ready to take coverings.
- Due to different geometries, a wide variety of covering heights can be catered for. The profiles can be bent and shortened to length on-site.
- PROCURVE elements are designed to take mechanical loads (e.g. knocks, impacts and similar) along the edges of floors and wall coverings and to protect adjacent coverings.

4 Instructions

General Surface Prep

Choose PROCURVE square-edged profiles to suit the thickness of the intended flooring/covering. For installation, the upper edge of the profile must always be at the same height or lower than the adjacent covering edges. Check the profile for damage. Use only undamaged profiles. To cut to the required length and deburr, use suitable tools, clamps, saws or cutting devices as well as personal protective equipment.

For bends and curves, the PROBEND bending device is recommended as an ideal aid for creating radii. Generally, the profiles can also be bent by hand and/or using templates (e.g. made from chipboard) or similar.



The stamped holes at regular intervals along the fitting strip serve as a means of additional attachment of the profiles using steel pins or screws along the planned, curved line. It is recommended that the profiles are first adapted to the desired radii and then bonded.

Application of Product

ProCurve

Place the PROCURVE square-edged profile with the stamped fitting strip equally in the fresh bonding compound and align. Then cover over completely. The flooring/covering material adjacent to the fitting strip must be laid so it is completely embedded.

If the surface as a whole has a joint pattern, the joint to the profile can be formed to match the joint width, though it should be no wider than 2 mm.

The joint between the flooring/covering and the profile should be filled completely with grout.

Clean away any mortar/grout and adhesive residue immediately and completely using clean water and a non-abrading sponge pad or cloth from the sides of the profile on display. Bonding and joint filling substances should not dry onto the surface. Do not use abrasive bonding and joint filling substances.

5 Product Warranty

GUARANTEED QUALITY SATISFACTION

LIMITED PRODUCT WARRANTY



CUSTOM®

PROCURVE™

Custom Building Products ("Custom") warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a **period of one year following the date of original purchase**. CUSTOM's sole liability under this warranty shall be limited to the replacement of the product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with CUSTOM's printed instructions.

CUSTOM makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state.

