

# AQUA MIX® STANDARD RECOMMENDATION FOR: EPOXY GROUT INSTALLATIONS

---

## MAINTENANCE - ROUTINE

**Purpose:** Routine cleaning of CEG-Lite™ 100% Solids Commercial Epoxy Grout and 100% Solids Epoxy Grout installations

**Product Recommendation:** Aqua Mix® Concentrated Stone & Tile Cleaner

**Equipment:** Sponge or synthetic mop and bucket with wringer or floor scrub machine with white nylon scrub pads

**Coverage:** Approximately 10,000 - 20,000 sq. ft. per gallon

### Procedure:

1. Sweep or vacuum surface.
2. Mix 2 to 4 ounces of Concentrated Stone & Tile Cleaner per gallon of water.
3. Apply solution onto surface.
4. Allow to dwell 3 to 5 minutes on heavy soiled areas.
5. Agitate with sponge or synthetic mop. A floor scrub machine may be used on large commercial area using a white nylon scrub pad.
6. Remove dirty solution with a mop. A wet/dry vac may be used to pick up cleaning solution.
7. Rinse thoroughly with clean water, changing water every 500 sq. ft. or as needed.

## MAINTENANCE - PERIODIC HEAVY-DUTY

**Purpose:** Heavy-duty cleaning of CEG-Lite™ 100% Solids Commercial Epoxy Grout and 100% Solids Epoxy Grout installations

**Product Recommendation:** Aqua Mix® Heavy-Duty Tile & Grout Cleaner

**Equipment:** Synthetic mop and bucket with wringer and scrub brush or floor scrub machine with white nylon scrub pads

**Coverage:** Approximately 500 - 600 sq. ft. per gallon

### Procedure:

1. Sweep or vacuum surface.
2. Mix 1 part of Heavy-Duty Tile & Grout Cleaner to 5 parts water.
3. Apply solution onto surface.
4. Allow to dwell 3 to 5 minutes on heavy soiled areas.
5. Agitate with mop, scrub brush or using a floor scrub machine using a white nylon scrub pad.
6. Remove dirty solution with a mop. A wet/dry vac may be used to pick up cleaning solution.
7. Rinse thoroughly with clean water, changing water every 100 sq. ft. or as needed.

*These recommendations are intended as general guidelines for the care and maintenance of all above listed grout installations. The actual product dilution ratios and maintenance requirements may vary depending on the use and contaminants common to the area. **READ PRODUCT DIRECTIONS THOROUGHLY PRIOR TO USE. ALWAYS TEST FIRST.***

The information in this bulletin is presented in good faith, but no warranty, express or implied, is given nor is freedom from any patent in as much as any assistance furnished by CUSTOM with reference to the safe use and disposal of its products provided without charge. Custom Building Products assumes no obligation or liability therefore, except to the extent that any such assistance shall be given in good faith.



Technical Bulletin  
Technical Services 800-282-8786  
custombuildingproducts.com