

# Setting glass tile has never been so clear.

- ✓ CONSISTENT WHITE
- ✓ SUPERIOR BOND STRENGTH
- ✓ MINIMAL SHRINKAGE
- ✓ EXCEEDS ANSI A118.4, A118.11 AND A137.2 WHEN MIXED WITH WATER



Maximize the beauty of your customer's glass tile investment. **CUSTOM** brand Glass Tile Premium Thin-Set Mortar is designed specifically for the unique attributes of glass, spreading smoothly to provide full coverage behind the tile while delivering color consistency and superior bond strength. Work with the leader in performance-driven installation systems and support.

**CONSISTENT WHITE, CONSISTENT PERFORMANCE.  
WE KNOW GLASS TILE. COUNT ON CUSTOM.**



**CUSTOM**<sup>®</sup>

custombuildingproducts.com  
800-272-8786



# Glass Tile Premium Thin-Set Mortar

Glass Tile Premium Thin-Set Mortar offers the ultimate in bond strength for the most demanding installation requirements for larger format glass tile, mosaics and other difficult to bond tile and stone. Glass Tile Mortar is specifically formulated to provide a consistent bright white backdrop for clear, iridescent and translucent glass tile to accentuate its brilliance and beauty.

FEATURES	BENEFITS
Consistent White	Color-controlled process provides consistent bright white color for the entire application
Unsurpassed Bond Strength	Superior bond strength and minimal shrinkage ideal for smooth glass tile
Superior Non-sag / Non-slip Performance	Superior bond strength keeps the glass tiles in place when applied in vertical installations
Excellent Handling	Smooth and creamy formula delivers an easy to trowel mortar ensuring proper coverage
Exceeds ANSI A118.4, A118.11 and A137.2 Requirements	High performance thin-set formulated specifically for glass tile and other impervious materials

## Uses (Tile Types)

- Glass Tile
- Other impervious and hard to bond to tiles; porcelain, metal, synthetic and natural stone
- Vitreous, semi-vitreous or non-vitreous tile; ceramic, mosaic, quarry, cement body tile brick and stone veneer cement-based precast terrazzo

## Areas of Use

- Interior or exterior floors, walls or countertops
- Concrete, mortar beds, masonry, Portland cement plaster
- WonderBoard® and other cement backerboards
- Liquid applied waterproofing membranes such as RedGard® and Custom 9240®
- Crack prevention sheet membranes such as Crack Buster Pro®
- Exterior grade plywood
- Gypsum wallboard (dry areas only)
- Existing ceramic tile and fully bonded sheet vinyl flooring
- Plastic laminates and cutback adhesive

## Standards

- Exceeds ANSI A118.4, A118.11 and A137.2 standards without the need for additives
- ISO 13007-2



## Approximate Coverage

TROWEL SIZE	MINIMUM COVERAGE
1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) Square-Notch	50 - 55 sq. ft. / 25 lbs. (4.6 - 5.1 M <sup>2</sup> / 11.34 kg)
1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	35 - 39 sq. ft. / 25 lbs. (3.3 - 3.6 M <sup>2</sup> / 11.34 kg)
1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) Square-Notch	25 - 28 sq. ft. / 25 lbs. (2.3 - 2.6 M <sup>2</sup> / 11.34 kg)

## Ordering Information

ITEM CODE	SIZE	COLOR
GTMW25	25 lb. (11.34 kg) Bag	White

**CONSISTENT WHITE, CONSISTENT PERFORMANCE.  
WE KNOW GLASS TILE. COUNT ON CUSTOM.**



**CUSTOM®**

custombuildingproducts.com  
800-272-8786