REMOVAL OF TIRE DRESSING MARKS FROM PORCELAIN TILES

Tire Dressing is commonly used in new car showrooms during the detailing process. Tire dressing is generally sprayed on the car's tires and can be accidentally sprayed onto a porcelain tile floor. Once the tire dressing cures on the porcelain tile, it can be very difficult to remove.

With proper attention, Aqua Mix® NanoScrub® can be used to remove the tire dressing and any black markings. NanoScrub® is a water-based, abrasive cleaner with no VOCs. It's also non-toxic, non-flammable and non-acidic.

Any stains from the tire dressing should be treated within 24 hours. Following these simple directions will remove the tire dressing, leaving a clean porcelain tile floor.

- 1. Always test a small area first.
- 2. Protect surrounding areas from splattering to minimize clean-up.
- 3. Pre-wet contaminated surface area with water.
- 4. Apply a small amount of NanoScrub® onto the affected damp area, making thin slurry.
- 5. Spread mixture onto surface and agitate by hand using a good white nylon scrub brush or pad.
- 6. Pick up cleaning solutions with a clean sponge and rinse twice with clean water.
- Polish surface dry with clean, dry cotton towels, or buff dry with soft microfiber towels.
- 8. Repeat this process as needed to remove heavy surface contamination.

The information in this bulletin is presented in good faith, but no warranty, express or implied, is given nor is freedom from any patent in as much as any assistance furnished by CUSTOM® with reference to the safe use and disposal of its products provided without charge. Custom® Building Products assumes no obligation or liability therefore, except to the extent that any such assistance shall be given in good faith.



Technical Bulletin

Technical Services 800-282-8786 custombuildingproducts.com